



## Product Description

Berger Everglow is a high performance, long lasting wall paint with a beautiful low sheen finish that is smooth to the touch, very low odor and easy to clean. It has outstanding scrub resistance and excellent dirt resistance, making it a perfect finish for hard-use areas like kitchens, bathrooms and children's rooms.

## Design Use

Areas of use: Interior and Exterior  
Substrate: New plaster, brickwork, concrete, particle board, masonry and primed metal surfaces.

## Physical Data

Finish: Smooth with low sheen  
Colour: White and any colour in the Berger Colour World Tinting System.  
Spread Rate: 11.0 m<sup>2</sup>/L (White) and up to 15.0m<sup>2</sup>/L (colours). Practical coverage depends on the porosity and texture of the surface. Some colours may require a primer. This is indicated on the Colour World Chart.  
Drying Time: Touch: 15 minutes; recoat, 1 hour.  
Gloss Level: 13 - 20 (60°) Low Sheen

## Application Data

Ensure adequate ventilation during application and drying. Do not apply when humidity exceeds 95% and condensation is likely. Use up to 250 ml clean water for thinning if necessary for ease of application.

Brush or Roller: Apply an even coat, taking care to avoid runs and sags.  
Spray: Use conventional spray equipment.

## Additional Information

Thinner: Clean water  
Storage: Store in a cool, shaded, dry area.  
Hazard Rating: Non-flammable, non-toxic and lead-free  
Shelf Life: 2 years  
Pack Size: 0.95L, 3.8L, 19L

## Surface Preparation

The performance of this coating is directly related to the degree of surface preparation.

### Concrete, Plaster, Masonry

#### New surfaces

Smooth new surfaces, removing any loose sand, mortar splashes manually or mechanically. Prime new surfaces with one coat of Berger Grip & Seal, or for properties on or near the sea, prime with Berger Alkali Sealer or Berger Luxatex Salt Inhibitive primer after the surface has been allowed to weather for a minimum of 30 days. Berger Concrete Primer or Berger Tex Primer are also good primers for new concrete surfaces, allowed to cure for at least 45 days.

#### Previously Painted Surfaces

Ensure surface is clean, dry and free from dust, grease, algae, dirt and all other contaminants. Treat fungal growth, with Berger Sterilizing Solution. Surfaces showing cracking, peeling, chalking or efflorescence should be wire brushed, scraped and sanded to remove loose, flaking material, and reduced previous film to a flat finish. Thoroughly dust down the entire surface; then apply one coat of Berger Alkali Sealer. To achieve a very smooth interior or exterior surface, apply one or two coats of Berger Joint Compound. Use Berger Exterior Surface Compound or Berger Ready-to-Use All Purpose Crack Filler to fill holes, cracks and imperfections. Sand mechanically or manually to a smooth, clean surface, removing all dust and loose particles.

### WOOD

#### New surfaces

Sand new surfaces to a smooth finish. Prime lightly coloured wood with Berger Wood Primer, Berger Undercoat White or Berger Grip & Seal and dark wood with Berger Alkali Sealer or Berger Luxatex Primer. Allow recommended time for drying.

### Previously Painted Surfaces

Ensure that dirt, stains, loose material and contaminants, etc., are removed. If the surface is cracking or peeling, remove the loose material by scraping. Thoroughly dust to ensure a clean surface. Treat any fungal growth with Berger Sterilizing Solution. Apply one coat of Berger Wood Primer, Berger Grip & Seal, Berger Alkali Sealer or Berger Luxatex Primer, allowing recommended time for drying.

### GYPSUM

Sand to a smooth finish and remove all dust. Apply one coat of Berger Alkali Sealer or Berger Luxatex Primer to seal surface, allowing recommended time for drying.

### METAL SURFACES

IRON AND STEEL - should be thoroughly cleaned to remove all oil, grease, rust, scale moisture. Prime with Berger Metal Primer (Red Oxide/Yellow)  
 ALUMINIUM & ZINC - should be degreased and etched with Berger Self Etch Primer. Contact Berger Technical Service Department for other specific recommendations.

### Application

Apply two coats of Berger Everglow Low Sheen Emulsion to properly prepared new or previously painted surfaces.

### Health & Safety

**READ DIRECTIONS CAREFULLY BEFORE USE**  
 Do not take internally. Liquid paint and vapours may cause irritation. Use only with adequate ventilation. To ensure the entry of fresh air, open all windows and doors. If headache or dizziness is experienced, use respiratory protection or leave area for fresh air. Avoid contact with skin or eyes.

### First Aid

Ingestion: Do not induce vomiting. Get medical attention immediately.  
 Inhalation: If excessive exposure symptoms are experienced, leave area to obtain fresh air. If difficulty continues, seek immediate medical attention.  
 Eye Contact: Flush immediately with water for at least 15 minutes.  
 Skin Contact: Wash thoroughly with soap and water.

### Recommended paint solution for painting new, cured concrete or plaster - Step 1

**For priming new, cured, concrete or plaster surface**



Prime new, cured, concrete or plaster surface with **Berger Concrete Primer**. Tinting recommended for application under dark colours.

**For priming wall close to or by the sea**



Apply 1 coat of **Berger LUXATEX Salt Inhibitive Primer**

### Recommended paint solution for painting new wood, wall or metal - Step 1



Prime new wood, wall or metal surface with **Berger Grip & Seal Multi-Surface Primer**. A quick drying, water-based primer for many surfaces.

### Step 2

#### For priming metal



Apply 2 coats of **Berger Everglow**

### Contact Us



**Berger Paints Barbados Ltd.**  
 Exmouth Gap, Brandons, St. Michael, Bridgetown, Barbados, W.I. BB12069  
 Tel: +1-246-425-9073  
 Fax: +1-246-228-0866  
 Email: info@bergeronline.com

[www.bergercaribbean.com](http://www.bergercaribbean.com)

[facebook.com/BergerCaribbean](https://www.facebook.com/BergerCaribbean)

These suggestions and data are based on information we believe to be reliable. They are offered in good faith but without guarantee, as conditions and methods of use of our products are beyond our control. We recommend that the prospective user determine the suitability of our materials and suggestions before adopting them on a commercial scale. Suggestions for uses of our products should not be understood as recommendations that they be used in violation of any patent or regulations. For specific recommendations, contact your Berger Technical Service Representative or Technical Service Department.